

DROP WIRE CLAMP

- Used to strain relieve telephone drop wire
- Designed to be used to support 1 through 6 pair drop wires
- Removable
- Stainless steel or aluminum construction, metal or plastic shim
- 3 piece or 2 piece (captive shim) construction



Patented captive shim design prevents incorrect installation



| Part Number | Material | Shim | Shim Material | Number of Pairs/Clamp | Carton Qty | Carton Size | Carton Weight |
|-------------|-----------------|-----------|-----------------|-----------------------|------------|-----------------------|---------------|
| SI-0956 | Stainless Steel | Removable | Stainless Steel | 2 | 250 | 18" x 8 1/2" x 4 1/2" | 23 Lbs. |
| SI-0956P | Stainless Steel | Removable | Plastic | 2 | 250 | 18" x 8 1/2" x 4 1/2" | 23 Lbs. |
| SI-0957 | Stainless Steel | Removable | Plastic | 1 | 250 | 18" x 8 1/2" x 4 1/2" | 23 Lbs. |
| SI-0959 | Aluminum | Removable | Aluminum | 2 | 250 | 18" x 8 1/2" x 8 1/2" | 17 Lbs. |
| SI-0959P | Aluminum | Removable | Plastic | 2 | 250 | 18" x 8 1/2" x 8 1/2" | 22 Lbs. |
| SI-0961 | Stainless Steel | Captive | Stainless Steel | 2 | 250 | 19" x 9" x 5" | 24 Lbs. |
| SI-0965 | Stainless Steel | Captive | Stainless Steel | 3 | 200 | 19" x 9" x 5" | 22 Lbs. |
| SI-0966 | Stainless Steel | Removable | Stainless Steel | 6 | 200 | 19" x 9" x 5" | 34 Lbs. |
| SI-0968 | Stainless Steel | Captive | Stainless Steel | 6 | 200 | 19" x 9" x 5" | 34 Lbs. |

FIBER DROP WIRE CLAMP

- Used to strain relieve fiber drop wire
- Removable
- Stainless steel construction
- Patent pending

| Part Number | Carton Qty | Carton Size | Carton Weight |
|-------------|------------|-----------------------|---------------|
| SI-0972 | 50 | 13 1/2" x 5" x 5 1/4" | 22 Lbs. |



MESSENGER DROP CLAMP

- Used to support messenger drop cable between the pole, mid-span and house
- Accepts RG 6, RG 6Q, RG 11 and RG 59, with .061" or .072" diameter messenger wire
- Stainless steel wire, aluminum body
- 700lb. pull capacity
- Patented

| Part Number | Carton Qty | Carton Size | Carton Weight |
|--------------|------------|--------------------------|---------------|
| SI-0969 | 100 | 9" x 7" x 7" | 5 Lbs. |
| SI-0969INS | 100 | 9 1/2" x 9 1/2" x 7 1/2" | 7 Lbs. |
| SI-0969INS-1 | 2000 | 14" x 14" x 10" | 28 Lbs. |



SI-0969



SI-0969INS

SI-0969INS-1

DRIVE HOOK

Belcore Specification: 7365

Product Number PID Number:
SI-3000 400 314 530

- Used for securing drop wire attachments and service drops
- Rolled fetter drive threads and pilot point for easy starting
- Drive hooks are galvanized for long service life

| Part Number | Size | Carton Qty | Carton Size | Carton Weight |
|-------------|---------------|------------|--------------------|---------------|
| SI-3000 | 3/4" x 4 1/2" | 200 | 9" x 9" x 7" | 53 Lbs. |
| SI-3001 | 3/4" x 3 1/2" | 500 | 11" x 11" x 7 1/2" | 46 Lbs. |



CABLE SUSPENSION CLAMP

Belcore Specification: 8623

PID Number: 400 762 282

- Designed to securely grip messenger cable
- Clamps accept 1/2" (6.6M) to 3/4" (16M) messenger strand

- Made from rolled steel, galvanized for maximum corrosion protection
- Furnished with two 1/2" track bolts and square nuts
- Mount messenger assembly to pole with a 3/8" bolt thru center hole

| Part Number | Carton Qty | Carton Size | Carton Weight |
|-------------|------------|--------------|---------------|
| SI-1740 | 25 | 9" x 9" x 7" | 45 Lbs. |



Curved Cable Suspension Clamp

Product Number: SI-1750

PID Number: 400 762 274

| Part Number | Type | Carton Qty | Carton Size | Carton Weight |
|-------------|------------|------------|--------------|---------------|
| SI-1750 | Heavy Duty | 10 | 9" x 9" x 7" | 36 Lbs. |
| SI-1755 | Economy | 25 | 9" x 9" x 7" | 53 Lbs. |



GUY HOOK

Belcore Specification: 7909

Part Number PID Number:
SI-4425 400 149 910
SI-4426 400 149 928

- Used for down and span guys
- Constructed of ductile iron, hot dip galvanized per ASTM A-153
- Features smooth grooves to eliminate chafing of the strand
- Accepts a wide range of strand diameters

| Part Number | Size | Carton Qty | Carton Size | Carton Weight |
|-------------|------|------------|----------------|---------------|
| SI-4425 | 3/4" | 25 | 12" x 9" x 5" | 41 Lbs. |
| SI-4426 | 1" | 25 | 14" x 10" x 8" | 44 Lbs. |

