

# Orange/Clear Suction & Discharge Hose



- Application:** Water Suction & Discharge [rental/construction pumping and fish suction]
- Construction:** Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.
- Temperature:** -13°F to + 140°F
- Features:**
- Clear sidewall permits visual check of material flow
  - Rated for both suction & discharge
  - External helix provides for easy drag
  - Lightweight and flexible

Part #	ID	OD	Weight	Std. Length	Working Pressure	Vacuum Rating	Min Bend Radius
	(in)	(in)	(lbs/ft)	(ft)	(psi)	(in/HG)	(in)
JJG-JBDJ-JAJJ	1-1/2	2.03	0.47	100	110	29	2.5
JJG-JCBJ-JAJJ9	2	2.60	0.69	100	100	29	4
JJG-JDJJ-JAJJ	2-1/2	3.01	0.74	100	100	29	5
JJG-JDHJ-JAJJ9	3	3.70	1.13	100	100	28	6
JJG-JHDJ-JJHJ9	4	4.78	1.74	100	80	28	7
JJG-JIFJ-JJGB9	6	7.17	3.88	20,60,100	70	28	10
JJG-ABHJ-JJFJ9	8	9.34	5.55	20,25	60	28	16
JJG-AFJJ-JJDJ9	10	11.63	8.90	20,25	40	28	25